



ENGINE
POWER



57 Hp

HYDRAULIC
SYSTEM



80 l/min

HYDRAULIC
CAPACITY



2100 Kg
(with counterweights)

BOOM
HEIGHT



3200 mm

STANDARD SET-UP

| | |
|--|------------------------------|
| Engine | Kohler KDI 1903TCR / STAGE V |
| Power Hp | 42 @ 2600 RPM |
| Speed km/h | 30 |
| Hydrostatic transmission - 4WD | Standard |
| Electric differential lock | Standard |
| Water cooling | Standard |
| Hydraulic selflevelling | Standard |
| Hydraulic system l/min | 80 |
| Joystick | 10 funzioni |
| 12V power outlet + 165W power outlet (front) | Standard |
| Working LED lights (2 front + 1 rear) | Standard |
| Digital dashboard | Standard |
| Adjustable ergonomic seat with belts + armrest | Standard |
| Double speed wheel motors | Standard |
| Metal hoods (front/rear) | Standard |
| Integrated counterweights 95Kg | Standard |
| Tractor wheels | 31x15.00-50 |
| Dimensions | 3153x1500x2138mm |
| Weight Kg (with counterweights) | 2500 |

CODE WITH STANDARD SET-UP

P 5 7 1 2 0 0 0 0 2